



Perfectly stowed away in the provided storage case.



Immaculate weld seams with the UNIFLOOR E (Vietnam).

Hot air welder

UNIFLOOR E / UNIFLOOR S

With UNIFLOOR E you can weld floor coverings made of PVC-P, PE, linoleum and modified thermoplastics, without any reconfiguration, up to 24.6 ft per minute. It is reliable, technically perfect and easy to handle.

- b Reproducible results thanks to digital display of set and actual values
- b Electronically controlled heating
- b Steplessly controlled air flow (only UNIFLOOR E)
- b All floor coverings welded without reconfiguration
- b Automatic start
- b Integrated wall switch






Technical Data

Voltage	V~	120
Power	W	1800
Temperature	°F	68 – 1148
Speed	ft/min	3.3 – 24.6
Air flow range	%	50 – 100
Size (L W H)	inch	16.5 10.6 8.5
Weight	lbs	24.2 (with 10 ft cord)
Conformity marking		2
Approval mark		3
Certification scheme		CCA
Protection class I		1

Article No.:

- 115.024 UNIFLOOR E 120V / 1800 W, squeezed nozzle, without plug, temperature in °C
- 116.133 UNIFLOOR E 120V / 1800 W, squeezed nozzle, without plug, temperature in °F
- 115.038 UNIFLOOR S 120V / 1800 W, squeezed nozzle, without plug, temperature in °C

Accessories UNIFLOOR E

	115.054	Welding rod de-reeler
	115.057	Trolley attachment
	114.224	Floor welding nozzle, optimised for PVC material
	115.342	Floor welding nozzle, for PVC and PUR material
	103.394	Floor welding nozzle air-knife, optimised for PUR material
	103.602	Heating element, 120 V / 1800 W
	126.448	Storage case 23.8 x 19 x 12.3 inch multi-layer plate, green (included in delivery)