



TIVERTON, RI
TOLL FREE: (888) 807-4030

ANDOVER, MA
TOLL FREE: (800) 289-7505




MINOR BLOWER

WITH MAJOR PERFORMANCE

MINOR BLOWER



MINOR BLOWER
WITH DIODE PID



Technical Data

Air supply for max. one Labor S or one Diode PID or one Diode S		
Order #	11D	
Voltage	V~	42,120,230
Power consumption	W	90, 90, 90
Frequency	Hz	50/60
Air Flow	l/min	400, 50/60Hz
Pressure Stat.	Pa	4000, (40mbar), 50/60Hz
Emission level	LpA(dB)	67
Size	mm	250x95, handle Ø 64
Weight	kg	1.15 with cord

MINOR BLOWER: The **LEISTER** Minor Blower is a robust compact mini blower designed to provide a steady source of blown air to the Leister hot air tools. It can withstand the harsh environments subjected to it by installers of flooring, roof membranes, geomembrane liners and plastic welding technicians. Power supply is 120V with a on/off switch and a removable air intake filter. The blower runs on a small carbon brushed motor. Carbon brushes can easily be changed once they wear out. Life expectancy of the blower depends on the working conditions. OD of the air output nipple on the blower is 15 mm or 5/8".