

LEISTER Medium Pressure Blower SILENCE



Technical data Blower SILENCE

Design	Radial blower		
Voltage for three-phase supply	V~	3×380–440	3×230
Voltage for single-phase supply	V~	1×230	
Capacitor for single-phase supply	µF	12	
Frequency	Hz	50/60	
Power consumption	W	250	
Air flow at 20°C	l/min.	4700/6000	
Static pressure	Pa	1000/1400	
Ambient temperature	°C	< 60	
Noise emission level	LpA (dB)	61	
Environmental protection (IEC 529)		IP 54	
Outside diameter air inlet	mm	ø 80	
Outside diameter air outlet	mm	ø 60	
Weight	kg	9.0	
Size (L×W×H)	mm	280.5×289×280	

LEISTER Medium Pressure Blower ASO



Technical data Blower ASO

Design	Radial blower		
Voltage for three-phase supply	V~	3×380–440	3×230
Voltage for single-phase supply	V~	1×230	
Capacitor for single-phase supply	µF	25	
Frequency	Hz	50/60	
Power consumption	W	550	
Air flow at 20°C	l/min.	13500/15900	
Static pressure	Pa	1600/2400	
Ambient temperature	°C	< 60	
Noise emission level	LpA (dB)	70	
Environmental protection (IEC 529)		IP 54	
Outside diameter air inlet	mm	ø	134
Outside diameter air outlet	mm	ø	38
Weight	kg	15.0	
Size (L×W×H)	mm	357×387×368	

