

**GHIBLI** □

The universal tool



CE

**Technical Data**

<b>Type</b>	<b>Ghibli</b>	
Voltage	V~	100, 120, 200, 230
Power consumption	W	1500, 1500, 1500, 2000
Frequency	Hz	50 / 60
Temperature	°C	20 – 600, steplessly controlled
Air flow	l/min.	Level 2: 300 Level 3: 350
Pressure stat.	Pa	Level 2: 1500 (15 mbar) Level 3: 2100 (21 mbar)
Emission level	LpA (dB)	67
Size	mm	160 × 195 × 92, handle ø 57
Weight	kg	1.2 with 3 m cord
Approval mark:		CCA certified

Acceleration of the drying process of varnish, paint and filler with the GHIBLI.

**Hot air blower**

**ELECTRON** □

Powerful but still small



CE

**Technical Data**

<b>Type</b>	<b>Electron</b>	
Voltage	V~	42, 120, 200, 230
Power consumption	W	1000, 2700, 3000, 2300/3400
Frequency	Hz	50/60
Temperature	°C	20 – 650, steplessly controlled
Air flow	l/min.	max. 500, manual air slide
Pressure stat.	Pa	3000 (30 mbar)
Emission level	LpA (dB)	65
Size	mm	320 × 95, handle ø 64
Weight	kg	1.5 with 3 m cord
Approval mark:		



Fitting of a PVC sheer rail to a boat with the ELECTRON.



Effortless and smokeless removal of under-floor sealant with the ELECTRON.